

Chapter 10

LIBSERVICED System Log Messages

This chapter describes messages generated by the Services Physical Interface Cards (PICs) process (serviced), which provides the user interface for management and configuration of J20 gateway GPRS support node control (GGSN-C) PICs.

LIBSERVICED_CLIENT_CONNECTION on page 65

LIBSERVICED_OUTBOUND_REQUEST on page 65

LIBSERVICED_SNMP_LOST_CONNECTION on page 66

LIBSERVICED_SOCKET_BIND on page 66

LIBSERVICED_SOCKET_PRIVATIZE on page 66

LIBSERVICED_CLIENT_CONNECTION

System Log Message	LIBSERVICED_CLIENT_CONNECTION: Client connection error: <i>reason</i>
Description	An attempt to establish a client connection failed.
Type	Error: An error occurred
Severity	error

LIBSERVICED_OUTBOUND_REQUEST

System Log Message	LIBSERVICED_OUTBOUND_REQUEST: Outbound request failed for command [<i>request-string</i>]: <i>reason</i>
Description	There was an error while attempting to execute a command on a remote client.
Type	Error: An error occurred
Severity	error

LIBSERVICED_SNMP_LOST_CONNECTION

System Log Message	LIBSERVICED_SNMP_LOST_CONNECTION: Connection closed while receiving from client <i>client-number</i>
Description	A client connection was abruptly closed by the remote client while reading a message.
Type	Error: An error occurred
Severity	error

LIBSERVICED_SOCKET_BIND

System Log Message	LIBSERVICED_SOCKET_BIND: <i>library-function</i> : unable to bind socket <i>socket-descriptor</i> or: <i>reason</i>
Description	An attempt to bind a server socket for receiving client requests failed.
Type	Error: An error occurred
Severity	error

LIBSERVICED_SOCKET_PRIVATIZE

System Log Message	LIBSERVICED_SOCKET_PRIVATIZE: Unable to attach socket <i>socket-descriptor</i> to management routing instance: <i>reason</i>
Description	An attempt to attach a socket to the management routing instance for communication between the Routing Engine and GGSN-C PICs failed.
Type	Error: An error occurred
Severity	error